

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of obtaining channel estimates, the method comprising:
receiving, at a receiver, a preamble across a channel, the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in a frequency domain, the preamble including two or more training sequences;
performing a Fourier transform of the training sequences;
deriving initial channel estimates in the frequency domain with the received preamble and a stored preamble;
receiving, at the receiver, data symbols across the channel;
demodulating and decoding the data symbols; and
updating the channel estimates using the demodulated and decoded data symbols.
2. (Currently Amended) The method of claim 1, wherein said updating the channel estimate comprises updating the channel estimate by [[.]]performing operations on the demodulated and decoded data symbols, the operations excluding multiplication operations.
3. (Original) The method of claim 2, wherein the operations include addition and shift operations.
4. (Cancelled)
5. (Currently Amended) The method of claim 1, further comprising averaging the two or more training sequences of the received preamble.

6. (Original) The method of Claim 5, wherein averaging the two training sequences may be expressed as:

$$\bar{P}_k = \frac{(\bar{P}_k + \bar{P}_{k+N/2})}{2} \text{ for } k = 0, 1, 2, \dots, N/2 - 1, \text{ where } \bar{P}_k$$

represents a first received preamble sequence in the time domain, and $\bar{P}_{k+N/2}$ represents a second received preamble sequence.

7. (Original) The method of Claim 1, wherein the channel is in an orthogonal frequency division multiplexing (OFDM) system.

8. (Cancelled)

9. (Currently Amended) The method of Claim 1, wherein the received preamble comprises a pre-determined number of excited subcarriers and non-excited subcarriers.

10. (Currently Amended) The method of Claim 9, wherein the received preamble comprises excited subcarriers for subcarriers $k = +/-2, +/- 4, \dots +/-100$.

11. (Currently Amended) The method of Claim 9, further comprising interpolating the channel estimates for the ~~unexcited~~ non-excited subcarriers.

12. (Currently Amended) The method of Claim 1, ~~further comprising transmitting wherein the received preamble comprises~~ an orthogonal frequency division multiplexing symbol of the preamble, ~~the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in the frequency domain,~~ the received preamble comprising two or more training sequences in the time domain.

13. (Currently Amended) The method of Claim 12, wherein the received preamble in a frequency domain is

$$\bar{P}_k \begin{cases} \pm 1 & \text{for } k = \pm 2, \pm 4, \dots \pm 100 \\ 0 & \text{for } k = 0, \pm 1, \pm 3, \dots \pm 99, \pm 101, \pm 102, \dots, \pm 127, -128 \end{cases}$$

where k is a subcarrier number.

14. (Original) The method of Claim 1, further comprising using the two or more training sequences for correlation, wherein the two or more training sequences are identical.

15. (Original) The method of Claim 1, wherein said demodulating yields \bar{P}_k for $k = 0, +/-1, +/-2, \dots, +/-63, -64$.

16. (Previously presented) The method of Claim 1, further comprising linearly interpolating the channel estimates as expressed by $\bar{H}_{2k+1,0} = \frac{(\bar{H}_{2k,0} + \bar{H}_{2k+2,0})}{2}$,

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

17. (Original) The method of Claim 1, further comprising using decoded, decision data symbols to update the channel estimates.

18. (Original) The method of Claim 1, further comprising using data symbols decoded using a Viterbi algorithm to update the channel estimates.

19. (Original) The method of Claim 1, further comprising using Kalman adaptive filtering to update the channel estimates.

20. (Previously presented) The method of Claim 19, wherein a channel update may be expressed as

$$\bar{H}_{k,n+1} = \left(1 - \frac{1}{n} \right) \cdot \bar{H}_{k,n} + \frac{1}{n} \cdot \frac{\bar{Y}_{k,n}}{Dec(\bar{X}_{k,n})},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

21. (Original) The method of Claim 19, further comprising making a hard decision of which constellation point is closest to a received subcarrier in order to update the channel estimates.

22. (Original) The method of Claim 1, further comprising using a Least Mean Square adaptive filtering to update the channel estimates.

23. (Previously presented) The method of Claim 22, wherein a channel update is expressed as

$$\bar{H}_{k,n+1} = \begin{cases} \bar{H}_{k,n} + 2\mu(\bar{Y}_{k,n} - \bar{H}_{k,n}Dec(\bar{X}_{k,n}))Dec(\bar{X}_{k,n}^*) & \text{for } P_k \neq 0 \\ \bar{H}_{k,n} + 2\mu_1(\bar{Y}_{k,n} - \bar{H}_{k,n}Dec(\bar{X}_{k,n}))Dec(\bar{X}_{k,n}^*) & \text{for } P_k = 0 \end{cases},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

24. (Original) The method of Claim 1, further comprising using an exponential update adaptive filtering to update the channel estimates.

25. (Currently Amended) A communication device comprising:

a receiver;

a Fourier transform module operable to perform a Fourier transform of two or more training sequences received in a preamble in a frequency domain, wherein the preamble comprises a first group of excited subcarriers and a second group of subcarriers being set to zero in the frequency domain;

a channel estimator operable to derive initial channel estimates in the frequency domain using the received preamble and a stored preamble;

a decoder to demodulate and decode received data symbols; and

an update module operative to update the channel estimate using the demodulated and decoded data symbols.

26. (Original) The communication device of claim 25, wherein the update module is operative to update the channel estimate by performing operations on the demodulated and decoded data symbols, the operations excluding multiplication operations.

27. (Original) The communication device of claim 26, wherein the operations include addition and shift operations.

28. (Cancelled)

29. (Currently Amended) The communication device of claim 25, further comprising an averaging module to average the two or more training sequences of the received preamble.

30. (Original) The communication device of claim 29, wherein averaging the two training sequences may be expressed as:

$$\bar{P}_k = \frac{(\bar{P}_k + \bar{P}_{k+N/2})}{2} \text{ for } k = 0, 1, 2, \dots, N/2 - 1,$$

where \bar{P}_k represents a first received preamble sequence in the time domain, and $\bar{P}_{k+N/2}$ represents a second received preamble sequence.

31. (Original) The communication device of claim 25, wherein the channel is an orthogonal frequency division multiplexing (OFDM) channel.

32. (Cancelled)

33. (Currently Amended) The communication device of claim 25, wherein the received preamble comprises a pre-determined number of excited subcarriers and non-excited subcarriers.

34. (Currently Amended) The communication device of claim 33, wherein the received preamble comprises excited subcarriers for subcarriers $k = +/-2, +/-4, \dots +/-100$.

35. (Currently Amended) The communication device of Claim 33, wherein the channel estimator is operative to interpolate the channel estimates for the ~~unexcited~~ non-excited subcarriers.

36. (Currently Amended) The communication device of Claim 25, wherein the received preamble includes an orthogonal frequency division multiplexing symbol, ~~the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in the frequency domain,~~ the received preamble comprising two or more training sequences in the time domain.

37. (Currently Amended) The communication device of claim 36, wherein the received preamble in a frequency domain is

$$\bar{P}_k \begin{cases} \pm 1 & \text{for } k = \pm 2, \pm 4, \dots \pm 100 \\ 0 & \text{for } k = 0, \pm 1, \pm 3, \dots \pm 99, \pm 101, \pm 102, \dots, \pm 127, -128 \end{cases}$$

where k is a subcarrier number.

38. (Original) The communication device of claim 25, wherein the channel estimator is operative to use the two or more training sequences for correlation, wherein the two or more training sequences are identical.

39. (Original) The communication device of claim 25, wherein said demodulating yields \bar{P}_k for $k = 0, +/-1, +/-2, \dots, +/-63, -64$.

40. (Previously presented) The communication device of claim 25, wherein the channel estimator is operative to linearly interpolate the channel estimates as expressed by

$$\bar{H}_{2k+1,0} = \frac{(\bar{H}_{2k,0} + \bar{H}_{2k+2,0})}{2},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k .

41. (Original) The communication device of Claim 25, wherein the update module is operative to update the channel estimates using decoded, decision data symbols.

42. (Original) The communication device of claim 25, wherein the update module is operative to update the channel estimate using data symbols decoded using a Viterbi algorithm.

43. (Original) The communication device of claim 25, wherein the update module is operative to update the channel estimate using Kalman adaptive filtering.

44. (Previously presented) The communication device of claim 43, wherein a channel update may be expressed as

$$\bar{H}_{k,n+1} = \left(1 - \frac{1}{n} \right) \cdot \bar{H}_{k,n} + \frac{1}{n} \cdot \frac{\bar{Y}_{k,n}}{Dec(\bar{X}_{k,n})},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

45. (Original) The communication device of claim 43, wherein the update module is operative to make a hard decision of which constellation point is closest to a received subcarrier in order to update the channel estimates.

46. (Original) The communication device of claim 25, wherein the update module is operative to update the channel estimate using a Least Mean Square adaptive filtering.

47. (Previously presented) The communication device of claim 46, wherein a channel update is expressed as

$$\bar{H}_{k,n+1} = \begin{cases} \bar{H}_{k,n} + 2\mu(\bar{Y}_{k,n} - \bar{H}_{k,n}Dec(\bar{X}_{k,n}))Dec(\bar{X}_{k,n}^*) & \text{for } P_k \neq 0 \\ \bar{H}_{k,n} + 2\mu_1(\bar{Y}_{k,n} - \bar{H}_{k,n}Dec(\bar{X}_{k,n}))Dec(\bar{X}_{k,n}^*) & \text{for } P_k = 0 \end{cases},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

48. (Original) The communication device of claim 25, wherein the update module is operative to update the channel estimate using an exponential update adaptive filtering.

49. (Currently Amended) A communication device comprising:

means for receiving preambles and data symbols;

means for performing a Fourier transform of two or more training sequences received in a preamble, the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in a frequency domain;

means for deriving initial channel estimates in the frequency domain using the received preamble and a stored preamble;

means for demodulating and decoding received data symbols; and

means for updating the channel estimate using the demodulated and decoded data symbols.

50. (Original) The communication device of claim 49, further comprising means for updating the channel estimate by performing operations on the demodulated and decoded data symbols, the operations excluding multiplication operations.

51. (Original) The communication device of claim 50, wherein the operations include addition and shift operations.

52. (Cancelled)

53. (Currently Amended) The communication device of claim 49, further comprising means for averaging the two or more training sequences of the received preamble.

54. (Original) The communication device of claim 53, wherein averaging the two training sequences may be expressed as:

$$\bar{P}_k = \frac{(\bar{P}_k + \bar{P}_{k+N/2})}{2} \text{ for } k = 0, 1, 2, \dots, N/2 - 1,$$

where \bar{P}_k represents a first received preamble sequence in the time domain, and $\bar{P}_{k+N/2}$ represents a second received preamble sequence.

55. (Original) The communication device of claim 49, wherein the channel is an orthogonal frequency division multiplexing (OFDM) channel.

56. (Cancelled)

57. (Currently Amended) The communication device of claim 49, wherein the received preamble comprises a pre-determined number of excited subcarriers and non-excited subcarriers.

58. (Currently Amended) The communication device of claim 57, wherein the received preamble comprises excited subcarriers for subcarriers $k = +/-2, +/-4, \dots +/-100$.

59. (Currently Amended) The communication device of claim 57, further comprising means for interpolating the channel estimates for the ~~unexcited~~ non-excited subcarriers.

60. (Currently Amended) The communication device of claim 49, wherein the received preamble includes an orthogonal frequency division multiplexing symbol, ~~the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in the frequency domain~~, the received preamble comprising two or more training sequences in the time domain.

61. (Currently Amended) The communication device of claim 60, wherein the received preamble in a frequency domain is

$$\bar{P}_k \begin{cases} \pm 1 & \text{for } k = \pm 2, \pm 4, \dots \pm 100 \\ 0 & \text{for } k = 0, \pm 1, \pm 3, \dots \pm 99, \pm 101, \pm 102, \dots, \pm 127, -128 \end{cases}$$

where k is a subcarrier number.

62. (Original) The communication device of claim 49, further comprising means for using the two or more training sequences for correlation, wherein the two or more training sequences are identical.

63. (Original) The communication device of claim 49, wherein said demodulating yields \bar{P}_k for $k = 0, +/-1, +/-2, \dots, +/-63, -64$.

64. (Previously presented) The communication device of claim 49, further comprising means for linearly interpolate the channel estimates as expressed by

$$\bar{H}_{2k+1,0} = \frac{(\bar{H}_{2k,0} + \bar{H}_{2k+2,0})}{2},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k .

65. (Original) The communication device of claim 49, further comprising means for updating the channel estimates using decoded, decision data symbols.

66. (Original) The communication device of claim 49, further comprising means for updating the channel estimate using data symbols decoded using a Viterbi algorithm.

67. (Original) The communication device of claim 49, further comprising means for updating the channel estimate using Kalman adaptive filtering.

68. (Previously presented) The communication device of claim 67, wherein a channel update may be expressed as

$$\bar{H}_{k,n+1} = \left(1 - \frac{1}{n} \right) \cdot \bar{H}_{k,n} + \frac{1}{n} \cdot \frac{\bar{Y}_{k,n}}{Dec(\bar{X}_{k,n})},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

69. (Original) The communication device of claim 67, further comprising means for making a hard decision of which constellation point is closest to a received subcarrier in order to update the channel estimates.

70. (Original) The communication device of claim 49, further comprising means for updating the channel estimate using a Least Mean Square adaptive filtering.

71. (Previously presented) The communication device of claim 70, wherein a channel update is expressed as

$$\bar{H}_{k,n+1} = \begin{cases} \bar{H}_{k,n} + 2\mu(\bar{Y}_{k,n} - \bar{H}_{k,n}Dec(\bar{X}_{k,n}))Dec(\bar{X}_{k,n}^*) & \text{for } P_k \neq 0 \\ \bar{H}_{k,n} + 2\mu_1(\bar{Y}_{k,n} - \bar{H}_{k,n}Dec(\bar{X}_{k,n}))Dec(\bar{X}_{k,n}^*) & \text{for } P_k = 0 \end{cases},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

72. (Original) The communication device of claim 49, further comprising means for updating the channel estimate using an exponential update adaptive filtering.

73. (Currently Amended) A computer readable medium encoded with a computer program, product, tangibly embodied in an information carrier, for obtaining a channel estimate, the computer program product being operable to cause data processing apparatus to perform indicative of operations comprising:

performing a Fourier transform of two or more training sequences received in a preamble across a channel, the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in a frequency domain;

deriving initial channel estimates in the frequency domain with the received preamble and a stored preamble;

demodulating and decoding [[the]] data symbols received across the channel; and

updating the channel estimate using the demodulated and decoded data symbols.

74. (Currently Amended) The computer ~~program-product~~ readable medium of claim 73, wherein said updating the channel estimate comprises updating the channel estimate by performing operations on the demodulated and decoded data symbols, the operations excluding multiplication operations.

75. (Currently Amended) The computer ~~program-product~~ readable medium of claim 74, wherein the operations include addition and shift operations.

76. (Cancelled)

77. (Currently Amended) The computer ~~program-product~~ readable medium of claim 73, further comprising averaging the two or more training sequences of the received preamble.

78. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 77, wherein averaging the two training sequences may be expressed as:

$$\bar{P}_k = \frac{(\bar{P}_k + \bar{P}_{k+N/2})}{2} \text{ for } k = 0, 1, 2, \dots, N/2 - 1,$$

where \bar{P}_k represents a first received preamble sequence in the time domain, and $\bar{P}_{k+N/2}$ represents a second received preamble sequence.

79. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, wherein the channel is in an orthogonal frequency division multiplexing (OFDM) system.

80. (Cancelled)

81. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, wherein the received preamble comprises a pre-determined number of excited subcarriers and non-excited subcarriers.

82. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 81, wherein the received preamble comprises excited subcarriers for subcarriers $k = +/-2, +/-4, \dots +/-100$.

83. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 81, the operations further comprising interpolating the channel estimates for the ~~unexcited non-excited~~ subcarriers.

84. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, ~~further comprising transmitting wherein the received preamble comprises~~ an orthogonal frequency division multiplexing symbol ~~of the preamble, the preamble comprising a first group of excited subcarriers and a second group of subcarriers being set to zero in the frequency domain, the received preamble comprising two or more training sequences in the time domain.~~

85. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 84, wherein the received preamble in a frequency domain is

$$\bar{P}_k \begin{cases} \pm 1 & \text{for } k = \pm 2, \pm 4, \dots \pm 100 \\ 0 & \text{for } k = 0, \pm 1, \pm 3, \dots \pm 99, \pm 101, \pm 102, \dots, \pm 127, -128 \end{cases}$$

where k is a subcarrier number.

86. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, the operations further comprising using the two or more training sequences for correlation, wherein the two or more training sequences are identical.

87. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, wherein said demodulating yields \bar{P}_k for $k = 0, +/-1, +/-2, \dots, +/-63, -64$.

88. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, the operations further comprising linearly interpolating the channel estimates as expressed by

$$\bar{H}_{2k+1,0} = \frac{(\bar{H}_{2k,0} + \bar{H}_{2k+2,0})}{2},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

89. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, the operations further comprising using decoded, decision data symbols to update the channel estimates.

90. (Currently Amended) The computer ~~program-product~~ readable medium of claim 73, the operations further comprising using data symbols decoded using a Viterbi algorithm to update the channel estimate.

91. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, the operations further comprising using Kalman adaptive filtering to update the channel estimates.

92. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 91, wherein a channel update may be expressed as

$$\bar{H}_{k,n+1} = \left(1 - \frac{1}{n}\right) \cdot \bar{H}_{k,n} + \frac{1}{n} \cdot \frac{\bar{Y}_{k,n}}{Dec(\bar{X}_{k,n})},$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

93. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 91, the operations further comprising making a hard decision of which constellation point is closest to a received subcarrier in order to update the channel estimates.

94. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, the operations further comprising using a Least Mean Square adaptive filtering to update the channel estimates.

95. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 94, wherein a channel update is expressed as

$$\bar{H}_{k,n+1} = \begin{cases} \bar{H}_{k,n} + 2\mu(\bar{Y}_{k,n} - \bar{H}_{k,n} \text{Dec}(\bar{X}_{k,n})) \text{Dec}(\bar{X}_{k,n}^*) & \text{for } P_k \neq 0 \\ \bar{H}_{k,n} + 2\mu_1(\bar{Y}_{k,n} - \bar{H}_{k,n} \text{Dec}(\bar{X}_{k,n})) \text{Dec}(\bar{X}_{k,n}^*) & \text{for } P_k = 0 \end{cases}$$

where \bar{H}_k represents an estimated channel frequency response corresponding to a subcarrier k.

96. (Currently Amended) The computer ~~program-product~~ readable medium of Claim 73, the operations further comprising using an exponential update adaptive filtering to update the channel estimates.

97. (Original) The method of claim 1, wherein the method is performed in an IEEE 802.11a-compliant system.

98. (Original) The method of claim 1, wherein the method is performed in an IEEE 802.16a-compliant system.

99. (Previously presented) The device of claim 25, wherein the method is performed in an IEEE 802.11a-compliant system.

100. (Original) The device of claim 25, wherein the method is performed in an IEEE 802.16a-compliant system.

101. (Original) The device of claim 49, wherein the method is performed in an IEEE 802.11a-compliant system.

102. (Original) The device of claim 49, wherein the method is performed in an IEEE 802.16a-compliant system.

103. (Currently Amended) The computer ~~program-product~~ readable medium of claim 73, wherein the method is performed in an IEEE 802.11a-compliant system.

104. (Currently Amended) The computer ~~program-product~~ readable medium of claim 73, wherein the method is performed in an IEEE 802.16a-compliant system.